



The compact MICROMAG walk behind scrubber in the Conquest













Phone: (03) 9879 8089 Unit 7/15 Molan St. Ringwood, Vic. 3134 steamvictoria@optusnet.com.au www.steamvictoria.com.au











FEATURES

- Actuator driven scrub deck gives maximum down pressure and cleaning results on any floor surface. Saves operator manually raising and lowering the scrubbing deck.
- Heavy duty roto-moulded tanks are mounted onto steel chassis and don't incorporate part of the frame as in many scrubbers on the market today.
- Tilt back tank gives immediate access to all components.
 This makes daily maintenance and servicing a breeze.
- Heavy steel chassis is powder coated for maximum resilience to harsh environments and chemicals and all fasteners used are stainless steel.

SPECIFICATIONS	20TD
Theoretical cleaning capacity (m²/hr)	3060
Operation run time(hrs)	3
Cleaning width (mm)	510
Solution/Recovery tank (ltr)	38
Solution flow rate (I/min.)	0 – 2
Noise level (dB)	67
Power supply (v)	24
Brush pressure (kg)	0 - 70
Weight (kg)	350
Dimensions (I x w x h) (mm)	1020 x 460 x 970
Pad/brush (number/size) mm	1/510
Battery charger	Automatic
Drive	Traction
Brush speed (rpm)	200
Travel speed-forward (km/h)	0 - 6.0